

4418 CRUDE OIL WASTE PIT SUCTION HOSE

Choose
Smooth Cover 4418
OR
Corrugated Cover 4419



TUBE: NBR, NOT FOR REFINED PETROLEUM PRODUCTS

REINFORCEMENT: Spiraled synthetic plies with steel wire helix

COVER: SBR, Black

BRANDING: Jason Logo 4418 Crude Oil Waste Pit Suction - Do Not Use for Refined Petroleum. Orange Mylar Longitudinal Stripe

TEMPERATURE RANGE: -40°F (-40°C) to +150°F (+66°C)

FEATURES: Flexible, resistant to abrasion and weathering. Full 4:1 Safety Factor

APPLICATION: Where full suction is required. Great for applications handling crude oil, salt and fresh water, tank bottoms and diesel fuels. [Great for crude oil spill clean-up operations!](#)

STANDARD LENGTHS: 100 ft. **VACUUM RATING:** Full Vacuum all sizes

Part Number	I.D. in.	I.D. mm	O.D. in.	O.D. mm	Rein. Plies	Max W.P. PSI	Max W.P. BAR	Weight lb./ft.	Weight KG/m	Min. Bend Radius in.	Min. Bend Radius mm	Stock Item
4418-0200-100	2	50.80	2.47	62.74	2	150	10.34	0.99	1.47	8.00	203.20	Y
4418-0300-100	3	76.20	3.52	89.41	2	150	10.34	1.76	2.62	16.00	406.40	Y
4418-0400-100	4	101.60	4.52	114.81	2	150	10.34	2.29	3.41	18.00	457.20	Y