



# Jason Industrial Inc.®

A MEGADYNE GROUP COMPANY

## BIO-DIESEL SUCTION & DISCHARGE HOSE

Inhibits the Migration of Bio-Fuels Through the Hose Wall!



**Bio-Diesel is manufactured from plant oils, animal fats and recycled cooking oils. UHMWPE tube gives maximum resistance to todays bio-diesel blends.**

**TUBE:** Ultra-high molecular weight polyethylene

**REINFORCEMENT:** Synthetic fabric with 2-wire helix and two conductive copper wires

**COVER:** CR, smooth, black, oil, heat, ozone, weather and abrasion resistant

**BRANDING:** Jason Logo 4423 BIO-DIESEL 150 PSI WP DO NOT USE FOR ETHANOL

**TEMPERATURE RANGE:** -31°F (-35°C) to +176°F (+80°C)

**APPLICATION:** For suction and discharge of bio-diesel fuels

**LENGTHS:** 100 ft.

Part Number	I.D.		O.D.		Rein. Plies	Max W.P.		Weight		Min. Bend Radius		Stock Item
	in.	mm	in.	mm		PSI	BAR	lb./ft.	KG/m	in.	mm	
4423-0100-100	1	25.40	1.42	36.00	2	150	10.34	0.49	0.73	6.00	152.40	Y
4423-0150-100	1-1/2	38.10	1.93	49.00	2	150	10.34	0.75	1.12	8.00	203.20	Y
4423-0200-100	2	50.80	2.48	63.00	2	150	10.34	1.16	1.72	12.00	304.80	Y
4423-0300-100	3	76.20	3.50	89.00	2	150	10.34	1.81	2.69	18.00	457.20	Y



340 Kaplan Drive • Fairfield, NJ 07004-6004  
973-227-4904 • Fax: 973-227-1651

Distribution Center • Carol Stream, IL 60188  
630-752-0600 • Fax: 630-752-0680

Branch Offices - Florida/Texas: 813-241-4111 • California: 323-265-8061

[www.jasonindustrial.com](http://www.jasonindustrial.com)